

# LIFU

# 化成機 FORMING MACHINE

## MODEL RF

### 1.概要

本機是一種專供修補氧化皮膜之設備，定溫清潔隔離的環境下，用水性電解質做媒介，以電化學的方式，使鋁或鉭金屬表面產生或修補其氧化層

### 2.特徵

- (1)可調溫控耐腐蝕電熱管.
- (2)液位精密控制.
- (3)液體循環過濾.氣體過濾
- (4)節省能源:熱回收與水蒸氣的回收.
- (5)可依需要追加熱風罩防止水蒸氣凝結短路.
- (6)自動補液(純水).
- (7)定時裝置.
- (8)獨特的絕緣方式調整工作物之作業水平高度.
- (9)溫度可條 定溫+ 2攝氏度.



### 1.GENERAL CONCEPT

This machine is that one kind specializes in mending the equipment which oxidizes the cover layer, under the clean environment and isolated warmly definitely , use the electrochemistry. Again the aluminum or tantalum metal. The surface turning into or mending oxidizing layer .

### 2.PARTICULARS

- (1)Adjustable temperature-controlled and corrosion-resistant electric heat is managed.
- (2)Control accurately in the liquid location . (3)Liquid circulation filters and air filtration.
- (4)Save the energy: Heat retrieves the recovery with the vapor.
- (5)OPTION: Add to the hot wind to cover. Prevent the vapor condensing and shorting out.
- (6)Automatic fluid infusion ( Pure water). (7)Timer device .
- (8)the horizontal height is adjustable in insulating way. (9)Temperature control +- 2 degrees Centigrade.

### 適用規格 Specifications:

Application	Model	RF_Al	RF_Ta			
加工物 Element		鋁	鉭			
加工物框架 (Carrier specification)		指定	指定			
消耗電力 Power consumption		220V 3 50 OR 60 HZ 1HP ,Heater 5Kw~16Kw ( by appointed )				
消耗空氣 Air		No need				
機械尺寸 Machine size(cm)		L X W X H 2920X1200X2200	L X W X H 2920X900X2200			
淨 重 Net weight(kg)		780	780			

### 備 注:

- 1. 各種機型所適用規格於訂購時需加指定，其適用範圍請事先與本公司商洽。
- 2. 本公司保留機器修改或變更之權利。

### Remark :

- 1. Should be specified when ordering and pre-negotiation with our engineers on application range is required .
- 2. Any modification or change on machines may be adopted with- out notice .



### Manufacturer:

LIFU MACHINERY INDUSTRIAL CO.,LTD

立富精機股份有限公司

678,LIN SHEN RD.,WUFENG HSIANG,TAICHUNG HSIEN TAIWAN

TEL:886-4-23334274 FAX:886-4-23334293

E-mail: lifu7616@hotmail.com

http://www.lifu-lifu.com.tw