

LIFU

全自動鋼條整直機

AUTOMATIC STRAIGHTEN MACHINE

MODEL RF324

1.概要

本設備是專供固態電容 鋼條去焊點磨平後之鋼條重新整直整平 重複使用而設計 經數道轉輪滾壓軋直, 含自動夾輸送料及收料的專用設備.

2.特徵

- (1)人機介面觸控式設定.
- (2)送料輸Max:600片送入.
- (3)可調整鋼片彎曲度.
- (4)垂直自動供料1組.
- (5)收料夾輸滿料自動停機.
- (6)連續自動送出1組.
- (7)水平轉輪參組,



1.GENERAL CONCEPT

This is an automatic machine,For steel plate(stringer) straighten .

The parallel is drawn definitely.

Through 3 X axle roller straighten steel plate. With 3 Micro meter for adjustment use.

2.PARTICULARS

- (1) Touch panel setting working data.
- (2) Automatic feed control .
- (3)The radian can be adjusted.
- (4)Max. 600 pces input material cabin.
- (5)Shut down automatically.

When material of cabin was full.

適用規格 Specifications:

| Application | Model | RF324 | | | | |
|---------------------------------|-------|-------------------------|--|--|--|--|
| 製品外徑 width of products.(m/m) | | 9~13.5 | | | | |
| 製品厚度 Thickness of products(m/m) | | 0.3~1.0 | | | | |
| 製品長度 Length of products(m/m) | | 400~430 | | | | |
| 運轉速度 Production speed(pcs/min) | | 10~15 | | | | |
| 消耗電力 Power consumption | | 220V S 50 OR 60 HZ 200W | | | | |
| 消耗空氣 Air | | No need | | | | |
| 機械尺寸 Machine size(cm) | | L X W X H 210X60X150 | | | | |
| 淨重 Net weight(kg) | | 200~300 | | | | |

備注:

- 1. 此機型所適用鋼條寬度於訂購時需加指定, 其適用範圍請事先與本公司商洽 .
- 2. 本公司保留機器修改或變更之權利 .

Remark :

- 1. Width of products should be specified when ordering and pre-negotiation with our engineers on application range is re-quired .
- 2.Any modification or change on machines may be adopted with- out notice .



立富精機股份有限公司
 LIFU MACHINERY INDUSTRIAL CO.,LTD.
 台灣省台中縣霧峰鄉霧工三路10號
 10, WU GOING SAN ROAD., WU FENG HSIANG,
 TAICHUNG HSIEN, TAIWAN
 Tel:886-4-23334274 Fax:886-4-23334293
 E-Mail:lifu7616@hotmail.com